

SN-PA1B01-15

SIP Paging Adapter



Feature

- Two-way intercom communication
- Support 48K OPUS audio codec
- SIP & Onvif protocol compatibility
- Pre-recorded message (WAV/MP3)
- Alarm: GPIO, HTTP URL, and relay out
- Mic, headset and speaker interface
- Reset and volume control

Specification

Parameter	
Codec	OPUS 48 kHz, MP3 44.1 kHz, G.722 ADPCM 16 kHz, G.711 PCMU 8 kHz, G.711 PCMA 8 kHz
Security	Password protection, IP address filtering, Digest authentication, User access log, firewall
Network Protocol	SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP
Network Interface	10/100 Base-TX, RJ45
VoIP	Support for SIP protocol for integration with VoIP systems, integrated with SIP/PBX. 2 SIP accounts, SIP direct IP call, RTP multicast Codec: OPUS, MP3, G.722, PCMU, PCMA
Amplifier Description	Built-in 15W amplifier
Material	Metal
Power Supply	DC12V/24V or PoE
Interface	1-ch Mic input, 1-ch Headset output, 1-ch Speaker output, 2-ch GPIO alarm input, 1-ch GPIO alarm output, 2-ch Relay alarm output
Dimensions	112×105×29 mm
Weight	0.25 Kg
Languages	English