



SN-PA1H01-15

15W IP Horn Speaker



Overview

The Outdoor IP Speaker is nice looking with flat shape design. It's perfect to install in outdoor environment due to IP67 waterproof design. It can be applied to play background music, announcements, security or fire alarm linkage. The standard SIP protocol allows easy integration to other SIP devices.

Feature

- Produce loud and excellent sound
- IP67 waterproof design for installation in outdoors
- POE eliminates need for local power supply
- Compatible with VoIP, SIP devices (IPPBX, IP Phone) via SIP
- Compatible with IP Camera VMS via ONVIF
- Support Pre-recorded messages
- Support HPPT API for alarm in transmit

Specification

Audio	
Codec	OPUS 48 kHz, MP3 44.1 kHz, G.722 ADPCM 16 kHz, G.711 PCMU 8 kHz, G.711 PCMA 8 kHz
Speaker	
Max SPL	113 dB
Frequency response	300 Hz to 8 KHz
Frequency Range	500 to 2 KHZ $\pm$ 10 dB 400 to 12 KHZ $\pm$ 20 dB
Harmonic Distortion	0.1@1kHz
Signal to Noise Ratio	91 dB
Network	
Security	Password protection, IP address filtering, Digest authentication, User access log, firewall
Network Protocol	SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP
Network Interface	10/100 Base-TX, RJ45
VoIP	Support for SIP protocol for integration with VoIP systems, integrated with SIP/PBX. 2 SIP Accounts, SIP Direct IP Call, RTP Multicast Codec: OPUS, MP3, G.722, PCMU, PCMA
Amplifier	
Amplifier Description	Built-in 15W Amplifier
Alarm	
Alarm Input	1ch, When receiving a switch alarm, it can play a ringtone or a custom sound.
General	
Operating Temperature	-30°C to +60°C
Operating humidity	5% to 85%
Material	ABS + Metal (IP67 water-proof)
Rate Power	15W
Power Supply	POE(802.3af) or 12/24 VDC
Installation	Wall Mounted
Dimensions	240 × 165 × 225 mm (9.45 × 6.5 × 8.86 inch)
Net Weight	1.3 kg
Languages	English
Package Includes	Network Horn Speaker, User Manual

Dimensions (mm)

