

# SN-PA1W01-30

**30W IP Horn Speaker** 



#### **Overview**

The IP Wall Mounted Speaker can be installed horizontally or vertically, which makes it easy to mount on the exterior of building such as under eave. It's ideal for installation in school, offices, stores and hospitals. The built-in 30W amplifier transmits loud and excellent voice. It can be applied to play background music, announcements, security or fire alarm linkage. The standard SIP protocol allows easy integration to other SIP devices.

#### **Feature**

- Transfers especially loud and excellent sound
- IP 55 waterproof design for installation on exterior of building
- 48K OPUS Audio Codec enables excellent sound quality
- Compatible with VoIP, SIP devices (IPPBX, IP Phone) via SIP
- Compatible with IP Camera VMS via ONVIF
- Support Pre-recorded messages
- Support HPPT API for alarm in transmit

### **Specification**

Codec         OPUS 48 kHz, MP3 44.1 kHz, G.722 ADPCM 16 kHz, G.711 PCMU 8 kHz, G.711 PCMU 8 kHz           Speaker           Max SPL         105 dB           Frequency response         80 Hz to 20 KHz           Frequency Range         500 to 2 kHz ± 10 dB           Harmonic Distortion         0.1 @1 kHz           Signal to Noise Ratio         9 1 dB           Network         Vertwork           Security         Password protection, IP address filtering, Digest authentication, User access log, firewall           Network Protocol         SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP           Network Interface         10/100 Base-TX, RI45           ValP         Support for SIP protocol for integration with VoIP systems, integrated with SIP/PBX.           ValP         Support for SIP protocol for integration with VoIP systems, integrated with SIP/PBX.           ValP         Support for SIP protocol for integration with VoIP systems, integrated with SIP/PBX.           ValP         Support for SIP protocol for integration with VoIP systems, integrated with SIP/PBX.           ValP         Support for SIP protocol for integration with VoIP systems, integrated with SIP/PBX.           Aleman Input         4, When receiving a switch alarm, it can play a ringtone or a custom sound.           General         Support for Hoo'C           Operating humility <th>Audio</th> <th></th>	Audio	
Max SPL         105 dB           Frequency response         80 Hz to 20 KHz           Frequency Range         500 to 2 KHz ± 10 dB and to 12 KHz ± 20 dB           Harmonic Distortion         0.1 @1kHz           Signal to Noise Ratio         91 dB           Network           Security         Password protection, IP address filtering, Digest authentication, User access log, firewall           Network Protocol         SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP           Network Interface         10/100 Base-TX, RI45           VolP         Support for SIP protocol for integration with VoIP systems, integrated with SIP/PBX. 2 SUPA Accounts, SIP Direct IP Call, RTP Multicast codec: OPUS, MP3, G.722, PCMU, PCMA           Amplifier           Alarm           Alarm Input         1sh, When receiving a switch alarm, it can play a ringtone or a custom sound.           General           Operating Temperature         -30°C to +60°C           Operating humility         5% to 85%           Material         ABS + Metal (IP67 water-proof)           Rate Power         30W           Power Supply         POE+(802.3at) or 12/24 VDC           Installation         Wall Mounted           D	Codec	OPUS 48 kHz, MP3 44.1 kHz, G.722 ADPCM 16 kHz, G.711 PCMU 8 kHz, G.711 PCMA 8 kHz
Frequency response 80 Hz to 20 KHz Frequency Range 500 to 2 KHZ ± 10 dB 400 to 12 KHZ ± 20 dB Harmonic Distortion 0.1 @1kHz Signal to Noise Ratio 91 dB  Security Password protection, IP address filtering, Digest authentication, User access log, firewall Network Protocol SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP  Network Interface 10/100 Base-TX, RJ45 Support for SIP protocol for integration with VoIP systems, integrated with SIP/PBX. 2 SIP Accounts, SIP Direct IP Call, RTP Multicast code: OPUS, MP3, G.722, PCMU, PCMA  Amplifier  Alarm Input 1ch, When receiving a switch alarm, it can play a ringtone or a custom sound.  General  Operating Temperature -30°C to +60°C Operating humility 5% to 85% Material ABS + Metal (IP67 water-proof) Rate Power 30W Power Supply POE+(802.3at) or 12/24 VDC Installation Wall Mounted Dimensions 157 x 196 x 295 mm (6.18 x 7.72 x 11.61 inch) Net Weight 2.4 kg Languages English	Speaker	
Frequency Range 500 to 2 KHZ ± 10 dB 400 to 12 KHZ ± 20 dB  Harmonic Distortion 0.1 @1kHz  Signal to Noise Ratio 91 dB  Network  Security Password protection, IP address filtering, Digest authentication, User access log, firewall Network Protocol SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP  Network Interface 10/100 Base-TX, RJ45  VolP 25IP Accounts, SIP Direct IP Call, RTP Multicast Code: OPUS, MP3, G.722, PCMU, PCMA  Amplifier  Alarm Input 3ch, When receiving a switch alarm, it can play a ringtone or a custom sound.  General Operating Temperature -30°C to +60°C  Operating Temperature 30W  ABS + Metal (IP67 water-proof)  Rate Power 30W  Power Supply POE+(802.3at) or 12/24 VDC  Installation Wall Mounted  Dimensions 157 × 196 × 295 mm (6.18 × 7.72 × 11.61 inch)  Net Weight 2.4 kg  Languages English	Max SPL	105 dB
Frequency Range 400 to 12 KHZ ± 20 dB  Harmonic Distortion 0.1 @1kHz  Signal to Noise Ratio 91 dB  Network  Security Password protection, IP address filtering, Digest authentication, User access log, firewall Network Protocol SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP  Network Interface 10/100 Base-TX, RJ45  Support for SIP protocol for integration with VoIP systems, integrated with SIP/PBX. 2 SIP Accounts, SIP Direct IP Call, RTP Multicast Codec: OPUS, MP3, G.722, PCMU, PCMA  Amplifier  Alarm  Alarm 1nput 1ch, When receiving a switch alarm, it can play a ringtone or a custom sound.  General  Operating Temperature 30°C to +60°C  Operating Temperature 30°C to 58%  Material ABS + Metal (IP67 water-proof)  Rate Power 30W  Power Supply POE+(802.3at) or 12/24 VDC  Installation Wall Mounted  Dimensions 157 × 196 × 295 mm (6.18 × 7.72 × 11.61 inch)  Net Weight 2.4 kg  Languages English	Frequency response	80 Hz to 20 KHz
Signal to Noise Ratio 91 dB  Network  Security Password protection, IP address filtering, Digest authentication, User access log, firewall  Network Protocol SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP  Network Interface 10/100 Base-TX, RJ45  Support for SIP protocol for integration with VoIP systems, integrated with SIP/PBX. 2 SIP Accounts, SIP Direct IP Call, RTP Multicast Codec: OPUS, MP3, G.722, PCMU, PCMA  Amplifier  Amplifier Description Built-in 30W Amplifier  Alarm  Alarm  Ceneral  Operating Temperature -30°C to +60°C  Operating Temperature -30°C to +60°C  Operating humility S% to 85%  Material ABS + Metal (IP67 water-proof)  Rate Power 30W  Power Supply POE+(802.3at) or 12/24 VDC  Installation Wall Mounted  Dimensions 157 × 196 × 295 mm (6.18 × 7.72 × 11.61 inch)  Net Weight 2.4 kg  Languages English	Frequency Range	
Network           Security         Password protection, IP address filtering, Digest authentication, User access log, firewall           Network Protocol         SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP           Network Interface         10/100 Base-TX, RJ45           VolP         Support for SIP protocol for integration with VoIP systems, integrated with SIP/PBX. 2 SIP Accounts, SIP Direct IP Call, RTP Multicast Codec: OPUS, MP3, G.722, PCMU, PCMA           Amplifier           Amplifier Description           Built-in 30W Amplifier           Alarm           Alarm Input         1ch, When receiving a switch alarm, it can play a ringtone or a custom sound.           General           Operating Temperature         -30°C to +60°C           Operating humility         5% to 85%           Material         ABS + Metal (IP67 water-proof)           Rate Power         30W           Power Supply         POE+(802.3at) or 12/24 VDC           Installation         Wall Mounted           Dimensions         157 × 196 × 295 mm (6.18 × 7.72 × 11.61 inch)           Net Weight         2.4 kg           Languages         English	Harmonic Distortion	0.1 @1kHz
Security       Password protection, IP address filtering, Digest authentication, User access log, firewall         Network Protocol       SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP         Network Interface       10/100 Base-TX, RJ45         Support for SIP protocol for integration with VoIP systems, integrated with SIP/PBX. 2 SIP Accounts, SIP Direct IP Call, RTP Multicast Codec: OPUS, MP3, G.722, PCMU, PCMA         Amplifier       Amplifier Description         Alarm       Built-in 30W Amplifier         Alarm Input       1ch, When receiving a switch alarm, it can play a ringtone or a custom sound.         General       Operating Temperature       -30°C to +60°C         Operating humility       5% to 85%         Material       ABS + Metal (IP67 water-proof)         Rate Power       30W         Power Supply       POE+(802.3at) or 12/24 VDC         Installation       Wall Mounted         Dimensions       157 × 196 × 295 mm (6.18 × 7.72 × 11.61 inch)         Net Weight       2.4 kg         Languages       English	Signal to Noise Ratio	91 dB
Network Protocol       SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP         Network Interface       10/100 Base-TX, RJ45         VolP       Support for SIP protocol for integration with VoIP systems, integrated with SIP/PBX. 2 SIP Accounts, SIP Direct IP Call, RTP Multicast Codec: OPUS, MP3, G.722, PCMU, PCMA         Amplifier         Alarm         Alarm Input         1 ch, When receiving a switch alarm, it can play a ringtone or a custom sound.         General         Operating Temperature         Operating Inmility       5% to 85%         Material       ABS + Metal (IP67 water-proof)         Rate Power       30W         Power Supply       POE+(802.3at) or 12/24 VDC         Installation       Wall Mounted         Dimensions       157 × 196 × 295 mm (6.18 × 7.72 × 11.61 inch)         Net Weight       2.4 kg         Languages       English	Network	
Network Interface 10/100 Base-TX, RJ45  VoIP Support for SIP protocol for integration with VoIP systems, integrated with SIP/PBX. 2 SIP Accounts, SIP Direct IP Call, RTP Multicast Codec: OPUS, MP3, G.722, PCMU, PCMA  Amplifier  Amplifier Description Built-in 30W Amplifier  Alarm  Alarm Input 1ch, When receiving a switch alarm, it can play a ringtone or a custom sound.  General  Operating Temperature -30°C to +60°C  Operating humility 5% to 85%  Material ABS + Metal (IP67 water-proof)  Rate Power 30W  Power Supply POE+(802.3at) or 12/24 VDC  Installation Wall Mounted  Dimensions 157 × 196 × 295 mm (6.18 × 7.72 × 11.61 inch)  Net Weight 2.4 kg  Languages English	Security	Password protection, IP address filtering, Digest authentication, User access log, firewall
Support for SIP protocol for integration with VoIP systems, integrated with SIP/PBX. 2 SIP Accounts, SIP Direct IP Call, RTP Multicast Codec: OPUS, MP3, G.722, PCMU, PCMA  Amplifier  Amplifier Description Built-in 30W Amplifier  Alarm  Alarm Input 1ch, When receiving a switch alarm, it can play a ringtone or a custom sound.  General  Operating Temperature -30°C to +60°C  Operating humility 5% to 85%  Material ABS + Metal (IP67 water-proof)  Rate Power 30W  Power Supply POE+(802.3at) or 12/24 VDC  Installation Wall Mounted  Dimensions 157 × 196 × 295 mm (6.18 × 7.72 × 11.61 inch)  Net Weight 2.4 kg  Languages English	Network Protocol	SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP
VoIP2 SIP Accounts, SIP Direct IP Call, RTP Multicast Codec: OPUS, MP3, G.722, PCMU, PCMAAmplifierAmplifier DescriptionBuilt-in 30W AmplifierAlarmAlarm Input1ch, When receiving a switch alarm, it can play a ringtone or a custom sound.GeneralOperating Temperature-30°C to +60°COperating humility5% to 85%MaterialABS + Metal (IP67 water-proof)Rate Power30WPower SupplyPOE+(802.3at) or 12/24 VDCInstallationWall MountedDimensions157 × 196 × 295 mm (6.18 × 7.72 × 11.61 inch)Net Weight2.4 kgLanguagesEnglish	Network Interface	10/100 Base-TX, RJ45
Amplifier Description  Alarm  Alarm Input 1ch, When receiving a switch alarm, it can play a ringtone or a custom sound.  General  Operating Temperature -30°C to +60°C  Operating humility 5% to 85%  Material ABS + Metal (IP67 water-proof)  Rate Power 30W  Power Supply POE+(802.3at) or 12/24 VDC  Installation Wall Mounted  Dimensions 157 × 196 × 295 mm (6.18 × 7.72 × 11.61 inch)  Net Weight 2.4 kg  Languages English	VoIP	2 SIP Accounts, SIP Direct IP Call, RTP Multicast
Alarm Input 1ch, When receiving a switch alarm, it can play a ringtone or a custom sound.  General  Operating Temperature -30°C to +60°C  Operating humility 5% to 85%  Material ABS + Metal (IP67 water-proof)  Rate Power 30W  Power Supply POE+(802.3at) or 12/24 VDC  Installation Wall Mounted  Dimensions 157 × 196 × 295 mm (6.18 × 7.72 × 11.61 inch)  Net Weight 2.4 kg  Languages English	Amplifier	
Alarm Input 1ch, When receiving a switch alarm, it can play a ringtone or a custom sound.  General  Operating Temperature -30°C to +60°C  Operating humility 5% to 85%  Material ABS + Metal (IP67 water-proof)  Rate Power 30W  Power Supply POE+(802.3at) or 12/24 VDC  Installation Wall Mounted  Dimensions 157 × 196 × 295 mm (6.18 × 7.72 × 11.61 inch)  Net Weight 2.4 kg  Languages English	Amplifier Description	Built-in 30W Amplifier
Operating Temperature -30°C to +60°C Operating humility 5% to 85%  Material ABS + Metal (IP67 water-proof) Rate Power 30W Power Supply POE+(802.3at) or 12/24 VDC Installation Wall Mounted  Dimensions 157 × 196 × 295 mm (6.18 × 7.72 × 11.61 inch) Net Weight 2.4 kg Languages English	Alarm	
Operating Temperature -30°C to +60°C Operating humility 5% to 85% Material ABS + Metal (IP67 water-proof) Rate Power 30W Power Supply POE+(802.3at) or 12/24 VDC Installation Wall Mounted Dimensions 157 × 196 × 295 mm (6.18 × 7.72 × 11.61 inch) Net Weight 2.4 kg Languages English	Alarm Input	1ch, When receiving a switch alarm, it can play a ringtone or a custom sound.
Operating humility 5% to 85%  Material ABS + Metal (IP67 water-proof)  Rate Power 30W  Power Supply POE+(802.3at) or 12/24 VDC  Installation Wall Mounted  Dimensions 157 × 196 × 295 mm (6.18 × 7.72 × 11.61 inch)  Net Weight 2.4 kg  Languages English	General	
Material ABS + Metal (IP67 water-proof)  Rate Power 30W  Power Supply POE+(802.3at) or 12/24 VDC  Installation Wall Mounted  Dimensions 157 × 196 × 295 mm (6.18 × 7.72 × 11.61 inch)  Net Weight 2.4 kg  Languages English	Operating Temperature	-30°C to +60°C
Rate Power 30W  Power Supply POE+(802.3at) or 12/24 VDC  Installation Wall Mounted  Dimensions 157 × 196 × 295 mm (6.18 × 7.72 × 11.61 inch)  Net Weight 2.4 kg  Languages English	Operating humility	5% to 85%
Power Supply POE+(802.3at) or 12/24 VDC  Installation Wall Mounted  Dimensions 157 × 196 × 295 mm (6.18 × 7.72 × 11.61 inch)  Net Weight 2.4 kg  Languages English	Material	ABS + Metal (IP67 water-proof)
Installation Wall Mounted  Dimensions 157 × 196 × 295 mm (6.18 × 7.72 × 11.61 inch)  Net Weight 2.4 kg  Languages English	Rate Power	30W
Dimensions 157 × 196 × 295 mm (6.18 × 7.72 × 11.61 inch)  Net Weight 2.4 kg  Languages English	Power Supply	POE+(802.3at) or 12/24 VDC
Net Weight 2.4 kg Languages English	Installation	Wall Mounted
Languages English	Dimensions	157 × 196 × 295 mm (6.18 × 7.72 × 11.61 inch)
	Net Weight	2.4 kg
Package Includes Network Horn Speaker, User Manual	Languages	English
	Package Includes	Network Horn Speaker, User Manual

## **Dimensions (mm)**

