


# **SN-NVR5004E1**

**4CH 1HDD NVR** 



### **Key Features**

- Up to 4ch IP cameras access
- Up to 1-ch @ 6MP / 4-ch @ 1080P decoding capacity
- VGA/HDMI simultaneous video output
- 1 SATA hard disk up to 8TB
- 1 RJ45 10M/100M network interface
- Smart search & playback
- Support cloud upgrade







## Specification

Video Input		
IP Camera Input	4 Channel	
Incoming Bandwidth	40 Mbps	
Outgoing Bandwidth	40 Mbps	
Video Output		
HDMI Output	1920 × 1080, 1280 × 1024, 1024 × 768	
VGA Output	1920 × 1080, 1280 × 1024, 1024 × 768	
Decoding Capacity	1ch 6MP, 4ch 1080P@30fps	
Dual Stream	Support	
Multi-screen Display	1/4	
Recoding		
Resolution	6MP, 5MP, 4MP, 3MP, 1080P, 720P, D1 etc.	
Recording Mode	Manual, Schedule (Regular, Continuous), Event	
Trigger Events	Motion Detection, Video Loss, IVS	
Playback and Backup		
Sync Playback	4-ch	
Search Mode	Time /Date, Alarm, Picture grid, Event	
Backup Mode	USB Device, Network	
Network		
Network Function	HTTP, HTTPS, TCP/IP, IPv4, IPv6, UPnP, UDP, RTSP, SMTP, NTP, DNS, DHCP, P2P, IP Filter, DDNS, 802.1X, SNMP, PPPoE	
Remote Users	8 users	
Smart Phone	iOS, Android	
Interoperability	ONVIF, SDK	
Storage		
ANR	Support	
Interface		
HDD Interface	1 SATA interface, up to 8TB capacity for each disk	
Network Interface	1 RJ-45 (10/100 Mbps) self-adaptive Ethernet port	
USB	Rear panel: 2 × USB 2.0	
HDMI	1	

VGA	1
General	
Power Supply	DC12V/2A
Power Consumption	< 5 W (without HDD)
Operating Conditions	-10 °C to 50 °C (14 °F to 122 °F)
Storage Conditions	Less than 90% RH
Certifications	CE/FCC
Dimensions	254.5 × 224.4 × 43.9 mm (10.02 × 8.83 × 1.73 inch)
Net Weight	0.62 kg without HDD

### **Dimensions (mm)**





#### **Rear Panel**

