



SN-XVR3804E1

5MP 4CH 1HDD Hybrid DVR



Key Features

- Supports AHD, TVI, CVI, CVBS, IP video inputs
- Max. 6 channels IP camera inputs, each channel up to 4MP
- Up to 4 channels video stream perimeter protection
- Encoding ability up to 4K@ 7 fps, 5MP @ 12 fps, 4MP @ 15 fps, 1080P @ 30 fps
- Support 1-ch CVBS output, 1-ch VGA output, 1-ch HDMI output at up to 4K(3840 x 2160)
- Support HDMI and VGA simultaneous output
- Smart search & playback
- Support multiple languages




Specification

Video and Audio	
Analog Video Input	4-ch BNC interface, Supports coaxial control
AHD Input	8MP, 5MP, 4MP, 1080P, 720P
TVI Input	8MP, 5MP, 4MP, 1080P, 720P
CVI Input	8MP, 5MP, 4MP, 1080P, 720P
CVBS Input	PAL/NTSC
IP Video Input	2-ch (only IP up to 6-ch), each channel up to 4MP
HDMI Output	3840 × 2160, 1920 × 1080, 1280 × 1024, 1024 × 768
VGA Output	1920 × 1080, 1280 × 1024, 1024 × 768
CVBS Output	PAL/NTSC
Audio Input	4-ch, RCA
Audio Output	1-ch, RCA
Two-way Audio	Supported via RCA (Analog Input/Output)
Perimeter Protection	
Intrusion Detection	4-ch, support accurate detection of human and vehicle
Recording	
Encoding Resolution	4K, 5MP, 4MP, 1080P, 720P, 960H, D1, CIF
Frame Rate	4K @ 7fps, 5MP @ 12fps, 4MP @ 15fps, 1080P @ 30fps, 720P @ 30fps
Video Bit Rate	Main stream: 16 Kbps to 4096 Kbps, Sub stream: 16 Kbps to 1024 Kbps
Dual Stream	Support
Audio Compression	G.711
Playback and Backup	
Recording Mode	Manual, Alarm, Motion detection, Timing
Recording Playback	4/1
Search Mode	Time /Date, Alarm, Picture grid, Event
Backup Mode	USB Device, Network
Network	
Protocols	HTTP, HTTPS, TCP/IP, IPv4, IPv6, UPnP, UDP, RTSP, SMTP, NTP, DNS, DHCP, P2P, IP Filter, DDNS, 802.1X, SNMP

Remote Users	4
Smart Phone	iPhone, iPad, Android
Interoperability	ONVIF, SDK, CGI
Storage	
HDD	1 SATA interface
Capacity	Up to 8TB for each disk
Interface	
Network Interface	1 RJ45 10M/100M self-adaptive Ethernet Interface
Alarm In/Out	4/1
RS-485	1
USB Interface	3 ports (2 front USB 2.0 port, 1 rear USB 2.0 port)
General	
Power Supply	12 VDC/3A
Power Consumption	Max 15W (without HDD)
Working Temperature	-10 °C to 50 °C (14 °F to 122 °F)
Working Humidity	Less than 90% RH
Certifications	CE-EMC - EN 55032, EN IEC 61000-3-2, EN 61000-3-3, EN 55035 CE-LVD - EN IEC 62368-1 FCC 47 CFR Part 15 Subpart B
Dimensions (W×D×H)	255 × 240.8 × 44.45 mm (10.04 × 9.48 × 1.75 inch)
Net Weight	Approx. 0.9 kg (1.98 lb without HDD)

Dimensions (mm)



Rear Panel

