

STARLIGHT

Network Modules




Key Features

Deep Learning Algorithms



Face



Human



Vehicle



Smoke & Flame



Intrusion




Single Line Crossing



Double Line Crossing



Loitering



Wrong-way



Illegal Parking

People Counting



People Counting

Compatibility



Products

Ultra Starlight

40X SN-PMD2081DN-Z40	40X SN-PMD2046DN-Z40	37X SN-PMD2041DN-Z37
		
• 8 MP (3840 × 2160) @ 25/30 fps • 1/1.8" Sony STARVIS™ II CMOS • 40x optical, 16x digital • 6.8 mm to 272 mm • Face/Human/Vehicle/Smoke & Flame • EIS • Audio 1 in/out, alarm 1 in/out, RS485, CVBS, wiper, SD card slot • 149.8×65.6×75.8 mm (including tailboard)	• 4 MP (2592 × 1520) @ 50/60 fps • 1/1.8" Sony STARVIS™ II CMOS • 40x optical, 16x digital • 6.8 mm to 272 mm • Face/Human/Vehicle/Smoke & Flame • EIS • Audio 1 in/out, alarm 1 in/out, RS485, CVBS, wiper, SD card slot • 149.8×65.6×75.8 mm (including tailboard)	• 4 MP (2592 × 1520) @ 25/30 fps • 1/1.8" Sony STARVIS™ CMOS • 37x optical, 16x digital • 6.8 mm to 251mm • Face/Human/Vehicle/Smoke & Flame • EIS • Audio 1 in/out, alarm 1 in/out, RS485, CVBS, wiper, SD card slot • 140.8 x 56.8 x 66.4 mm (including tailboard)

Starlight

40X SN-PMD2053DN-Z40	30X SN-PMD2055DN-Z30	25X SN-PMD2020DN-Z25	15X SN-PMD2052DN-Z15
			
• 5MP (2592 × 1944) @ 25/30 fps • 1/2.8" Sony STARVIS™ II CMOS • 40x optical, 16x digital • 5 mm to 200 mm • Face/Human/Vehicle/Smoke & Flame • EIS • Audio 1 in/out, alarm 1 in/out, RS485, SD card slot • 114.7 x 53.5 x 62.5 mm (including tailboard)	• 5MP (2592 × 1944) @ 25/30 fps • 1/2.8" Sony STARVIS™ II CMOS • 30x optical, 16x digital • 5.3 mm to 159 mm • Face/Human/Vehicle/Smoke & Flame • Audio 1 in/out, alarm 1 in/out, RS485, SD card slot • 112.7 × 47.9 × 55.7 mm (including tailboard)	• 2MP(1920×1080) @ 25/30fps • 1/2.8" Sony STARVIS™ CMOS • 25x optical, 16x digital • 5 mm to 125 mm • Face/Human/Vehicle/Smoke & Flame • Audio 1 in/out, alarm 1 in/out, RS485, SD card slot • 110.8 x 48.1 x 55.7 mm (including tailboard)	• 5MP (2592 × 1944) @ 25/30 fps • 1/2.8" Sony STARVIS™ II CMOS • 15x optical, 16x digital • 5.3 mm to 79.5 mm • Face/Human/Vehicle/Smoke & Flame • Audio 1 in/out, alarm 1 in/out, RS485, CVBS, wiper, SD card slot • 92.6×49.1×57.8 mm (including tailboard)



Shenzhen Sunell Technology Corporation

22-23F, Building 2, Chongwen Park, Nanshan Zhiyuan (Phase 3), No. 3370 Liuxian Avenue, Nanshan District, Shenzhen 518052

+86(755) 2675 4336

+86(755) 8602 6152

sales@sunellsecurity.com

©2025 Shenzhen Sunell Technology Corporation. All rights reserved.

The specifications and descriptions of products and services contained in this catalogue were correct at the time of publishing. Inner Range reserves the right to change specifications or withdraw products without notice.