


Products



Accessories			
			
Bullet Bracket	PTZ Bracket	Pole Bracket	Corner Bracket
			
Glands	Flexible Conduit	Junction Box	Washing Tank

Application Scenarios



Oil Refining Plants



Chemical Plants



Oil & Gas Stations



Flour Mills



Ports



Oil Gas Exploitation



Shenzhen Sunell Technology Corporation

22-23F, Building 2, Chongwen Park, Nanshan Zhiyuan (Phase 3), No. 3370 Liuxian Avenue, Nanshan District, Shenzhen 518052

+86(755) 2675 4336 +86(755) 8602 6152 sales@sunellsecurity.com

©2025 Shenzhen Sunell Technology Corporation. All rights reserved.
The specifications and descriptions of products and services contained in this catalogue were correct at the time of publishing. Inner Range reserves the right to change specifications or withdraw products without notice.



Explosion-proof
Cameras



Key Features

Dual-certified

- Ex d II C T6 Gb / Ex tD A21 IP68 T80°C W



High Protection Level

- 316L Stainless Steel
- IP68



High Quality Imaging

- Ultra HD
- Excellent low-light performance



Intelligent Tracking

- Human/Vehicle
- Auto Tracking; Auto Focus




Edge AI


- IVS: Intrusion, Single Line Crossing, Double Line Crossing, Loitering, Wrong-way, Illegal Parking
- People counting



Face



Human



Vehicle



Smoke & Flame



Helmet & Safety Vest
(Optional)

Products

(Fiber-optic Optional)

Optical			
Bullet		IR Bullet	
	8MP SN-CHP8681CDN-Z40 • 8MP(3840×2160)@25/30fps • 1/1.8", 40x, 6.8-272mm		8MP SN-CHP8681CDR-Z40 • 8MP(3840×2160)@25/30fps • 1/1.8", 40x, 6.8-272mm • 100m IR
	5MP SN-CHP8650CDN-Z30 • 2592×1944 (5MP) @ 25/30fps • 1/2.8", 30x, 5.3 to 159mm		5MP SN-CHP8650CDR-Z30 • 2592×1944 (5MP) @ 25/30fps • 1/2.8", 30x, 5.3 to 159mm • 100m IR
IR Bullet		Speed Dome	
	8MP SN-CHP8681EBR-Z40 • 8MP(3840×2160)@25/30fps • 1/1.8", 40x, 6.8-272mm • 200m IR		5MP SN-IPS8652PCDN-Z15 • 2592×1944 (5MP) @ 25/30fps • 1/2.8", 15x, 5.3 to 79.5mm • Human/Vehicle/Smoke & Flame • Pan: 360°, Tilt: -10° to 90° • 100 VAC to 240 VAC
	5MP SN-CHP8650EBR-Z30 • 2592×1944 (5MP) @ 25/30fps • 1/2.8", 30x, 5.3 to 159mm • 200m IR		
PT		IR PT	
	8MP SN-IPT8681PAN-Z40 • 8MP(3840×2160)@25/30fps • 1/1.8", 40x, 6.8-272mm		8MP SN-IPT8681PAR-Z40 • 8MP(3840×2160)@25/30fps • 1/1.8", 40x, 6.8-272mm • 200m IR
	5MP SN-IPT8650PAN-Z30 • 2592×1944 (5MP) @ 25/30fps • 1/2.8", 30x, 5.3 to 159mm		5MP SN-IPT8650PAR-Z30 • 2592×1944 (5MP) @ 25/30fps • 1/2.8", 30x, 5.3 to 159mm • 200m IR
Thermal			
Bullet		Bi-spectrum PT	
	SN-TPH6406DA SN-TPH4203DA • 640×512/400×300 • Lens: 9(8)/15/25/35/50 mm • Human/Vehicle/Smoke & Flame • Temp. Pre-alarm & Alarm • Temp. Accuracy: ±2°C / ±2%		SN-TPT6436PA SN-TPT4233PA • Thermal: 640×512/400×300, Lens: 9(8)/15/25/35/50 mm • Optical: 2592×1944 (5MP) @ 25/30fps, 5.3 to 159 mm, 30x • 100m IR • Human/Vehicle/Smoke & Flame/Fire Spot • Temp. Pre-alarm & Alarm • Temp. Accuracy: ±2°C / ±2% • Pan: 360°, Tilt: -90° to 90°