



## High Way



### Solution



### Solution Topology



## Product Information



### 9MP ANPR Camera

- 1" GMOS
- 9MP(4096×2160)@50fps
- Fixed Lens, 25mm, 35mm, 50mm, motorized focus
- ANPR, up to 200km/h
- Vehicle attributes recognition
- Interface: 2 RJ45, 4/6 alarm input/output, 3 RS-485, 1 RS-232, 1 USB, 1 CVBS, SD card slot

### SN-CHP8290LAR



### Traffic Speed Radar

- Speed range 5 to 250km/h
- Covered lane up to 4 lanes
- 1 RS485, 1 RJ45
- 24GHz
- 9-32VDC

### SN-SMWR05S



### LED Strobe Supplement Light

- IR/white light flashing
- RS485 interface
- Flashing frequency ≥ 20 million times
- Supplement distance of 18-32m

### 4MP ANPR Bullet

- 1/1.8" Sony CMOS
- 4 MP(2592×1520)@60 fps
- 8-32mm, 10-50mm, auto-iris
- ANPR, up to 120km/h
- Vehicle attributes recognition
- Interface: Alarm, Wiegand, RS485, Audio
- 12 VDC, PoE(IEEE 802.3af)

### SN-IPR8047AKAN-T



### 4MP ANPR BOX

- 1/1.8" Sony CMOS
- 4 MP(2592×1520)@60 fps
- C/CS mount, fixed/DC iris
- ANPR, up to 120km/h
- Vehicle attributes recognition
- Interface: Alarm, RS485, Audio, CVBS
- 12 VDC, PoE(IEEE 802.3af)

### SN-IPR8047HAN-FT



### 4MP ANPR Bullet

- 1/2.8" Sony CMOS
- 4MP(2592×1520)@60 fps
- 2.7-13.5 mm, 5-50mm
- ANPR, up to 60km/h
- Detection and Capture: Face, Human, Vehicle, Smoke & flame
- Intelligent Analysis: Smart Motion, Intrusion, Single Line Crossing, Double Line Crossing, Loitering, Wrong-way, Illegal Parking, People counting

### SN-IPR8045DQAN-T



### 7" 8MP 40X IR Speed Dome

- 1/1.8" Sony CMOS
- 8 MP(3840×2160)@30 fps
- 40x, 6.8-272mm
- IR: 500m (1600 ft)
- Detection and Capture: Face, Human, Vehicle, Smoke & flame
- Intelligent Analysis: Smart Motion, Intrusion, Single Line Crossing, Double Line Crossing, Loitering, Wrong-way, Illegal Parking, People counting



## SunView CMS



### License Plate Library Management

Manage license plate grouping, license plate information, etc.




### License Plate Comparison Strategy

Manage license plate comparison strategies and configure various linkage parameters



### License Plate Library Management

Manage license plate grouping, license plate information, etc.



### Shenzhen Sunell Technology Corporation

22-23F, Building 2, Chongwen Park, Nanshan Zhiyuan (Phase 3), No. 3370 Liuxian Avenue, Nanshan District, Shenzhen 518052  
+86(755) 2675 4336 +86(755) 8602 6152 sales@sunellsecurity.com

©2025 Shenzhen Sunell Technology Corporation. All rights reserved.  
The specifications and descriptions of products and services contained in this catalogue were correct at the time of publishing. Sunell reserves the right to change specifications or withdraw products without notice.



## Intelligent Traffic System Solution



## Key Features

The intelligent traffic monitoring system stands as a crucial element of modern urban management, seamlessly integrating advanced technologies like high-definition visual technology, artificial intelligence, and big data analysis. It meticulously captures and interprets traffic information in real-time, empowering administrative departments to make precise decisions and facilitate efficient control. This system not only vastly enhances the effectiveness and accuracy of traffic governance but also infuses technological prowess into urban security, safeguarding public safety and expediting the transition towards smarter cities.

### Edge Intelligence



Onboard ANPR



Attributes Recognition



4000 Black/White List

### Flexible Application



Stand-alone

- Onboard ANPR algorithm
- Linkage barrier gate
- LPR Smart Search



Intelligent traffic solution


- Urban roadside
- Highway
- Parking lot
- Entrance & Exit



Third-party Integration

- CGI
- Wiegand, I/O, RS485

### High Performance & High Image Quality



9MP Global Shutter(SN-CHP8290LAR)



Starlight Sensor & 60fps



up to 200km/h(SN-CHP8290LAR)




Up to 3 lanes



Accuracy

- Capture rate ≥99%
- recognition accuracy ≥98%


## Parking Lot Management



## Road Monitoring



### Solution




Flexible Installation

- Installation height: 1~3m
- Capture distance: 2~6m
- Detection speed: <30km/h
- Supports pole mount, wall mount, ceiling mount



Barrier Control

- Onboard ANPR algorithm
- Up to 99% Accuracy
- Wiegand or I/O linkage barrier gate



Black/White List


- Supports white list, black list, visitor management
- Support for list event linkage



Parking Information Display

- CMS software to view parking information
- Displayed on the entrance and exit LED screen

### Solution Topology



### Solution



Vehicle LPR & Motorcycle LPR



Attributes Recognition



High Speed Capture



Smoke & Flame



Illegal Parking



Wrong-way Driving



Pedestrian Presence

### Solution Topology

