



SN-IPPVM24-B

24-inch Public View Monitor



Key Features

- Built-in HD(1080P) Camera, High-quality image display
- Image mode: Support uploading images and videos for playback
- Up to 1TB TF card
- IP camera video output, H.264/H.265 encoding type selection output
- Web upload ads for playback
- Support Chrome, Firefox, Edge browser playback
- Linux operating system, more stable and cost-effective
- Support POE and DC input, Wide power supply design, 12V±10% input

Specification

Panel	
Screen Size	23.8-inch
LED Type	LED
Screen Max. Resolution	1920 × 1080
Display Color	16.7 million colors
Brightness	250 cd/m ²
Monitor Aspect Ratio	16:9
Contrast Ratio	1000:1
Response Time	14ms
Visible Angle	H: 178°, V: 178°
Monitor Board	
Interface	Micro USB + TF + LAN + DC + Alarm Input / output + face alarm output + mobile detection alarm output + Emergency mode input
Speaker	8 Ω 3 Watt/channel
DC/PoE	12V DC±10%, PoE: 38 to 56V
OSD Languages	English, Chinese, Japanese
Power	< 30W
Wired Communication	1 × RJ45, 10/100 Mbps
Wireless Communication	WIFI
IP Camera	
Sensor	1/2.9", 2MP CMOS
Encoding format	H.264 / H.265
Effective Pixels	1920*1080
Browser	Support for Chrome, Firefox and Edge
Lens	3.3mm Fixed Lens
Integration protocol	ONVIF Profile S, API
Recording Resolution	1920 × 1080 @30fps
Motion Detection	Support
DVR Storage	up to 1TB TF card

EMMC/Flash	8GB
DDR/RAM	1GB
Function	
Image Settings	Chroma, contrast, brightness, sharpness, saturation Wide dynamics, backlight compensation, strong light suppression, 3D noise reduction
Video	You can choose to record normally and trigger motion detection/face detection/alarm input to record
Advertising	Support full-screen or half-screen image or video ads less than 1GB in size
Warning Information and Logo	The warning information supports warning pictures and warning voices, and the logo picture can set the size and position of the picture
Other	
VESA Mounting Pattern	200 × 100 or 100 × 100, location centered on monitor body
Operating Temperature	32° to 104° (0℃ to 40℃)
Storage Temperature	-4° to 140° (-20℃ to 60℃)
Operating Humidity	10 to 85℃
Certifications	CE, FCC certificates
Installation Method	Wall
Dimensions	572 × 377 × 37 mm (22.52" × 14.84" × 1.46")
Net weight	6.38 KG
Gross Weight	7.8 KG

Dimensions

