



SN-CC73NKB

Network Control Keyboard



Key Feature

- 10.1" IPS capacitive touchscreen with 1280×800 resolution
- Supports H.264/H.265 decoding, up to 4×1080p@30fps, 9×720p@30fps, and 1×4K@60fps
- Compatible with ONVIF 2.4, VISCA, PELCO-D/P, and NDI protocols
- Supports up to 1024 device connections, PTZ control, presets, patrol, and pattern scanning
- USB flash drive upgrade support for easy maintenance
- Power input: 12V DC (5.5/2.1 mm), PoE powered (IEEE 802.3af compliant)
- Interfaces: RJ45 (10/100/1000 Mbps), RS-485/RS-232, HDMI output (v1.4), USB 3.0, 3.5 mm audio jack
- 4-axis joystick with programmable buttons for enhanced PTZ operation

Specification

General	
Operating System	Android 11
Screen Size	10.1" IPS capacitive touch screen
Display Resolution	1280 × 800
Decoding Capability	- Supports H.264/H.265 - Max H.264: 4 × 1080p @ 30 fps - Max H.264: 9 × 720p @ 30 fps - Max H.265: 1 × 4K @ 60 fps
Protocol	Supports ONVIF 2.4 / VISCA (full compatibility) / PELCO-D/P / NDI
Function	- Supports up to 1024 device connections - Preset support - PTZ control - Patrol - Multi-point scanning
System Settings	Supports USB flash drive upgrade
Interface	- RJ45 (10M/100M/1000M adaptive Ethernet) - Phoenix connector (Half-duplex RS-485) / RS232 - HDMI output (Version 1.4) - USB 3.0 - 3.5 mm headphone jack
Power Supply	DC 12V 2A ±10%, Standard 5.5/2.1 jack Supports PoE power receiving (IEEE 802.3af)
Power Consumption	< 15W, Standby Current: < 100 mA
Operating Temperature	-10 °C to 40°C (14°F to 104°F)
Operating Humidity	10% to 90% RH (non-condensing)
Storage Temperature	-40 °C to 60 °C (-40 °F to 140 °F)
Product Dimensions (W × D × H)	449.7 × 178.6 × 115.4 mm (17.71 × 7.03 × 4.54 in)
Net Weight	Approx. 1400 g (3.09 lb)

Dimensions (mm)