

SN-XVR3704E1

4-ch 1080P 1-HDD Hybrid DVR



Key Features


- Multi-format video inputs (AHD, TVI, CVI, CVBS, and IP)
- Up to 6-channel IP camera inputs, up to 1080P per channel
- Up to 5MP-N @ 10 fps recording
- HDMI and VGA simultaneous video output
- Audio over coaxial cable
- Smart search and playback
- Multiple languages

Specifications

Video & Audio	
Analog Video Input	4 × BNC (supports UTC coaxial control)
AHD Input	5MP, 4MP, 1080P, 720P
TVI Input	5MP, 4MP, 1080P, 720P
CVI Input	5MP, 4MP, 1080P, 720P
CVBS Input	PAL / NTSC
IP Video Input	2-ch (up to 6-ch in IP mode), up to 1080P per channel
Audio Input	1 × RCA; up to 4-ch audio over coaxial cable (TVI only)
Audio Output	1 × RCA
Two-way Audio	Supported via RCA
Audio Compression	G.711A / G.711U
Recording	
Recording Resolution	5MP-N, 4MP-N, 1080P, 720P, D1
Recording Frame Rate	5MP-N @ 10 fps, 4MP-N @ 15 fps, 1080P @ 15 fps
Video Bit Rate	Main stream: 16 Kbps to 2048 Kbps; Sub stream: 16 Kbps to 1024 Kbps
Dual Stream	Supported
Recording Mode	Manual, Scheduled, Event
Event	
Event Trigger	Motion Detection, Video Loss, Video Tampering, Exception
Event Linkage	Recording, Email, Buzzer, PTZ, Push Notification
Display	
Decoding Capability	1 × 4K, 4 × 4MP, 16 × D1
HDMI Output	3840 × 2160, 1920 × 1080, 1280 × 1024, 1024 × 768
VGA Output	1920 × 1080, 1280 × 1024, 1024 × 768
CVBS Output	1 × BNC
Video Output Mode	Simultaneous HDMI, VGA, and CVBS outputs
Display Layouts	1/4
Playback & Backup	
Simultaneous Playback	4-ch / 1-ch
Search Mode	Date/Time, Alarm, Picture, Event
Playback Control	Play, Pause, Fast Forward, Rewind, Slow Playback, Digital Zoom

Backup Mode	USB Device, Network
Network	
Network Interface	1 × RJ45, 10/100 Mbps self-adaptive Ethernet port
Protocols	HTTP, HTTPS, TCP/IP, IPv4, IPv6, UDP, RTSP, SMTP, NTP, DNS, DHCP, UPnP, DDNS, P2P, IP Filter, IEEE 802.1X, SNMP
Remote Users	Up to 4 users
Mobile Client	iOS, Android
Interoperability	ONVIF, SDK, CGI
Storage	
HDD Interface	1 × SATA interface
HDD Capacity	Up to 8 TB per HDD
Interface	
USB Interface	2 × USB 2.0 ports (1 front, 1 rear)
Reset Button	On-board reset button
General	
Power Supply	12 VDC, 2 A
Power Consumption	≤ 15 W (without HDD)
Operating Temperature	-10 °C to 50 °C (14 °F to 122 °F)
Operating Humidity	≤90% RH (Non-condensing)
Certifications	CE-EMC: EN 55032, EN IEC 61000-3-2, EN 61000-3-3, EN 55035 CE-LVD: EN IEC 62368-1 FCC: 47 CFR Part 15, Subpart B
Dimensions	254.5 × 231.9 × 43.9 mm (10.02 × 9.13 × 1.73 inch)
Net Weight	Approx. 0.68 kg (1.5 lb) without HDD

Dimensions (mm)



Rear Panel

